



Total creepage [mm]	317
Air-distance [mm]	165
Dry-flashover [kV]	85
Wet-flashover [kV]	50
Drywithstand [kV]	50
Wetwithstand [kV]	38
Impulse voltage [kV]	95
CONNECTION	I
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	145
B [mm]	210
C [mm]	482
D [mm]	100
DRAWN:	Stehlík J.
CHECKED:	Prokopec M.
DATE:	11.4.2014

U_N [kV]	17,5	PARALLEL ELEM.	1
Q_N [kvar]	(28,9 34,7)	SERIES GROUPS	9
C_N [μ F]	0,30 (-5/+10%)	WEIGHT [kg]	17
f_N [Hz]	50 60	LIQUID CAP. [kg]	6,9
I_N [A]	1,7 2,0	STANDARD	IEC 60871-1/05
BIL [kV]	LIVE CASE!	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (120 M Ω)		

DRAWING No.:	4K0736A	TYPE:	PUFFS 23-17,5/0,3
--------------	---------	-------	-------------------



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 01 Žamberk
Czech Republic

tel.: +420 465 673 111
fax.: +420 465 612 319
e-mail: zez@zez-silko.cz
http:// www.zez-silko.cz